

View Online at <https://aerobasegroup.com/nsn/5340-00-517-3424>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.750 inches

Second Leg Length:

0.880 inches

Second Leg Width:

2.000 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

Between 0.390 inches and 0.410 inches

Second Leg Distance Between Hole Centers Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.440 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.120 inches

First Leg Width:

2.000 inches

First Leg Corner Radius:

0.380 inches

First Leg Distance Between Hole Centers Along Width:

1.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.380 inches and 0.400 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

150.0 degrees

Special Features:

First leg holes threaded 1/4-20 unc-2b

Material:

Copper alloy or steel

Surface Treatment:

Enamel

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0