NSN 5340-00-517-5474

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-517-5474

| Cross Sectional Shape: |
|---|
| Square or rectangular recess |
| Width: |
| 8.560 inches |
| Edge Shape: |
| Rectangle, multi holes |
| Length: |
| 9.030 inches |
| Corner Radius: |
| 0.250 inches |
| |
| Hole Quantity Along Length: |
| 12 |
| Hole Quantity Along Width: |
| 12 |
| Distance Between Holes Along Length: |
| Between 1.295 inches and 1.305 inches |
| Distance Between Hole Centerline And First Hole Along Length: |
| Between 0.775 inches and 0.785 inches |
| Distance Between Hole Centerline And First Hole Along Width: |
| Between 0.845 inches and 0.855 inches |
| Distance From First Hole Centerline To End Along Length: |
| Between 1.025 inches and 1.135 inches |
| Distance From First Hole Centerline To End Along Width: |
| Between 1.145 inches and 1.155 inches |
| Inside Corner Radius: |
| 0.400 inches |
| Securing Device Type: |
| Turnlock fastener |
| Material: |
| Aluminum alloy 6061 |
| Material Specification: |
| Qq-a-250/11 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-c-5541, type 2, grade c, class 1 military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5340-00-517-5474

Access Cover - Page 2 of 2



Fiig:

A531c0

Mil-std (military Standard):

Mil-c-5541 spec.