NSN 5340-00-522-9966

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-522-9966

view Offilitie at https://derobasegroup.com/hsh/5540-60-522-5500
Cross Sectional Shape:
Flat
Hole Diameter:
0.128 inches
Width:
1.000 inches
Edge Shape:
Rectangle, four holes
Length:
1.031 inches
Corner Radius:
0.0625 inches
Distance Between Holes Along Length:
0.781 inches
Distance Between Holes Along Width:
0.750 inches
Distance From First Hole Centerline To End Along Length:
0.125 inches
Distance From First Hole Centerline To End Along Width:
0.125 inches
Body Thickness:
0.109 inches
Securing Device Type:
Threaded fastener
Mounting Opening Shape Style:
Unthreaded hole
Features Provided:
Observation facility
Special Features:
Mtg holes countersunk, 82 degreesto 0.225in. Diameter with dovetail groove, 0.047in. Deep, 0.875in. Long, 30 degreeangle both sides,
0.500in. Distance from groove centerline to end along length and one hole, 0.093in.Dia, 0.500in.Distance from hole centerline to end along
length and 0.062in. Distance from hole centerline to end along width
Material:
Aluminum alloy
Material Specification:
Qq-a-268, al24s federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 2, cl 2 military specification single treatment response
Fsc Application Data:

N/a

Periscope, tank
Shelf Life:

NSN 5340-00-522-9966

Access Cover - Page 2 of 2



		eas	

--

Demilitarization:

Yes - demil/mli

Fiig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.