NSN 5340-00-522-9966

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-522-9966

| view Offilitie at https://derobasegroup.com/hsh/5540-60-522-5500 |
|--|
| Cross Sectional Shape: |
| Flat |
| Hole Diameter: |
| 0.128 inches |
| Width: |
| 1.000 inches |
| Edge Shape: |
| Rectangle, four holes |
| Length: |
| 1.031 inches |
| Corner Radius: |
| 0.0625 inches |
| Distance Between Holes Along Length: |
| 0.781 inches |
| Distance Between Holes Along Width: |
| 0.750 inches |
| Distance From First Hole Centerline To End Along Length: |
| 0.125 inches |
| Distance From First Hole Centerline To End Along Width: |
| 0.125 inches |
| Body Thickness: |
| 0.109 inches |
| Securing Device Type: |
| Threaded fastener |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| Features Provided: |
| Observation facility |
| Special Features: |
| Mtg holes countersunk, 82 degreesto 0.225in. Diameter with dovetail groove, 0.047in. Deep, 0.875in. Long, 30 degreeangle both sides, |
| 0.500in. Distance from groove centerline to end along length and one hole, 0.093in.Dia, 0.500in.Distance from hole centerline to end along |
| length and 0.062in. Distance from hole centerline to end along width |
| Material: |
| Aluminum alloy |
| Material Specification: |
| Qq-a-268, al24s federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625, type 2, cl 2 military specification single treatment response |
| Fsc Application Data: |

N/a

Periscope, tank
Shelf Life:

NSN 5340-00-522-9966

Access Cover - Page 2 of 2



| | | eas | |
|--|--|-----|--|
| | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.