

View Online at <https://aerobasegroup.com/nsn/5340-00-523-2924>

Fabrication Method (non-core):

Machined

First Leg Length:

1.040 inches

Second Leg Length:

Between 2.720 inches and 2.760 inches

Second Leg Width:

1.720 inches

Second Leg Corner Radius:

Between 0.219 inches and 0.281 inches

First Leg Hole Diameter:

Between 0.105 inches and 0.110 inches

Second Leg Hole Diameter:

Between 0.129 inches and 0.132 inches

Second Leg Distance Between Hole Centers Along Width:

0.940 inches

Second Leg Distance Between Hole Centers Along Length:

1.630 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.385 inches and 0.415 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.405 inches and 0.435 inches

First Leg Thickness:

Between 0.045 inches and 0.050 inches

Second Leg Thickness:

Between 0.045 inches and 0.050 inches

First Leg Width:

Between 1.020 inches and 1.060 inches

First Leg Corner Radius:

Between 0.219 inches and 0.281 inches

First Leg Distance Between Hole Centers Along Width:

0.600 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.230 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0