

View Online at <https://aerobasegroup.com/nsn/5340-00-523-2924>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

1.040 inches

**Second Leg Length:**

Between 2.720 inches and 2.760 inches

**Second Leg Width:**

1.720 inches

**Second Leg Corner Radius:**

Between 0.219 inches and 0.281 inches

**First Leg Hole Diameter:**

Between 0.105 inches and 0.110 inches

**Second Leg Hole Diameter:**

Between 0.129 inches and 0.132 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.940 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.630 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.385 inches and 0.415 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.405 inches and 0.435 inches

**First Leg Thickness:**

Between 0.045 inches and 0.050 inches

**Second Leg Thickness:**

Between 0.045 inches and 0.050 inches

**First Leg Width:**

Between 1.020 inches and 1.060 inches

**First Leg Corner Radius:**

Between 0.219 inches and 0.281 inches

**First Leg Distance Between Hole Centers Along Width:**

0.600 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.210 inches and 0.230 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**Material:**

Titanium alloy

**Material Specification:**

Ams 4911 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0