

View Online at <https://aerobasegroup.com/nsn/5340-00-523-3440>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.970 inches and 0.990 inches

**Second Leg Length:**

Between 1.281 inches and 1.332 inches

**Second Leg Width:**

Between 1.626 inches and 1.708 inches

**Second Leg Corner Radius:**

Between 0.266 inches and 0.297 inches

**First Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 1.094 inches and 1.114 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.266 inches and 0.297 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.266 inches and 0.297 inches

**First Leg Thickness:**

Between 0.056 inches and 0.066 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.066 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.320 inches

**First Leg End Radius:**

Between 0.422 inches and 0.453 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0