

View Online at <https://aerobasegroup.com/nsn/5340-00-523-3440>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.970 inches and 0.990 inches

Second Leg Length:

Between 1.281 inches and 1.332 inches

Second Leg Width:

Between 1.626 inches and 1.708 inches

Second Leg Corner Radius:

Between 0.266 inches and 0.297 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.094 inches and 1.114 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.266 inches and 0.297 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.266 inches and 0.297 inches

First Leg Thickness:

Between 0.056 inches and 0.066 inches

Second Leg Thickness:

Between 0.056 inches and 0.066 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

0.320 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0