

View Online at <https://aerobasegroup.com/nsn/5340-00-526-0935>

Center To Center Distance Between Bolt Holes Along Width:

3.375 inches

Center To Center Distance Between Bolt Holes Along Length:

5.250 inches

End Application:

W/s: helicopter, iroquois uh-1; helicopter, chinook, ch-47; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p); helicopter, electronic countermeasures, eh-60a; aircraft, phantom f-4; helicopter observation (ahip), oh-58d; aircraft, stratofortress b-52; aircraft, stratolifter c-135

Wheel Quantity:

4

Safe Operating Load Rating:

500.0 pounds

Material And Location:

Steel dv506-115 fscm 11201

Wheel Type:

Solid

Wheel Diameter:

8.000 inches

Effective Height:

Between 10.156 inches and 10.344 inches

Features Provided:

Axle lubrication fitting and brake lock

Plate Style:

Rectangular

Wheel Bearing Type:

Roller or tapered roller

Swivel Bearing Arrangement:

One row

King Bolt Bearing Type:

Thrust

Tread Width:

2.000 inches

Caster Plate Length:

7.125 inches

Caster Plate Width:

5.000 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600