

View Online at <https://aerobasegroup.com/nsn/5340-00-526-0935>

**Center To Center Distance Between Bolt Holes Along Width:**

3.375 inches

**Center To Center Distance Between Bolt Holes Along Length:**

5.250 inches

**End Application:**

W/s: helicopter, iroquois uh-1; helicopter, chinook, ch-47; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p); helicopter, electronic countermeasures, eh-60a; aircraft, phantom f-4; helicopter observation (ahip), oh-58d; aircraft, stratofortress b-52; aircraft, stratolifter c-135

**Wheel Quantity:**

4

**Safe Operating Load Rating:**

500.0 pounds

**Material And Location:**

Steel dv506-115 fscm 11201

**Wheel Type:**

Solid

**Wheel Diameter:**

8.000 inches

**Effective Height:**

Between 10.156 inches and 10.344 inches

**Features Provided:**

Axle lubrication fitting and brake lock

**Plate Style:**

Rectangular

**Wheel Bearing Type:**

Roller or tapered roller

**Swivel Bearing Arrangement:**

One row

**King Bolt Bearing Type:**

Thrust

**Tread Width:**

2.000 inches

**Caster Plate Length:**

7.125 inches

**Caster Plate Width:**

5.000 inches

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A25600