

View Online at <https://aerobasegroup.com/nsn/5340-00-527-1928>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.640 inches and 0.660 inches

**Second Leg Length:**

Between 0.640 inches and 0.680 inches

**Second Leg Width:**

Between 0.610 inches and 0.630 inches

**First Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.300 inches and 0.320 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.270 inches and 0.290 inches

**First Leg Thickness:**

Between 0.058 inches and 0.066 inches

**Second Leg Thickness:**

Between 0.058 inches and 0.066 inches

**First Leg Width:**

Between 0.610 inches and 0.630 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.300 inches and 0.320 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.220 inches and 0.240 inches

**First Leg End Radius:**

Between 0.422 inches and 0.453 inches

**Second Leg End Radius:**

Between 0.422 inches and 0.453 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

167.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0