## NSN 5340-00-527-3207

Swivel Caster - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-527-3207

Center To Center Distance Between Bolt Holes Along Width:
3.375 inches
Center To Center Distance Between Bolt Holes Along Length:
5.250 inches
Wheel Quantity:
1
Safe Operating Load Rating:
670.0 pounds
Material And Location:
Steel plate err-100 err-100
Surface Treatment And Location:
Zinc plate err-100 err-100
Wheel Type:
Solid
Wheel Diameter:
8.000 inches
Effective Height:
10.500 inches
Features Provided:
Shock absorber and solid replaceable tire and swivel lock and swivel lubrication fitting
Plate Style:
Rectangular-countersunk ends
Wheel Bearing Type:
Roller
Swivel Bearing Type:
Annular ball
Swivel Bearing Arrangement:
One row
King Bolt Bearing Type:
Tapered roller
Tread Width:
2.500 inches
Caster Plate Length:
7.125 inches
Caster Plate Width:
5.250 inches
Caster Plate Mounting Hole Diameter:
0.594 inches
Style Designator:
Swivel offset
Shelf Life:

N/a

## NSN 5340-00-527-3207

Swivel Caster - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A25600