

View Online at <https://aerobasegroup.com/nsn/5340-00-530-8030>

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

Between 0.590 inches and 0.620 inches

**Second Leg Length:**

Between 0.810 inches and 0.820 inches

**Second Leg Width:**

Between 0.770 inches and 0.790 inches

**First Leg Hole Diameter:**

Between 0.069 inches and 0.730 inches

**Second Leg Hole Diameter:**

Between 0.108 inches and 0.114 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.245 inches and 0.255 inches

**Second Leg Distance Between Hole Centers Along Length:**

Between 0.495 inches and 0.505 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.135 inches and 0.145 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.069 inches and 0.730 inches

**First Leg Thickness:**

Between 0.075 inches and 0.085 inches

**Second Leg Thickness:**

Between 0.075 inches and 0.085 inches

**First Leg Width:**

Between 0.770 inches and 0.790 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.518 inches and 0.522 inches

**First Leg Distance Between Hole Centers Along Length:**

Between 0.310 inches and 0.314 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.125 inches and 0.135 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.405 inches and 0.415 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 1020

**Material Specification:**

Mil-s-7952 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, class 2 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-7952 spec.