

View Online at <https://aerobasegroup.com/nsn/5340-00-530-8030>

Mounting Hole Type:

Countersunk

First Leg Length:

Between 0.590 inches and 0.620 inches

Second Leg Length:

Between 0.810 inches and 0.820 inches

Second Leg Width:

Between 0.770 inches and 0.790 inches

First Leg Hole Diameter:

Between 0.069 inches and 0.730 inches

Second Leg Hole Diameter:

Between 0.108 inches and 0.114 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.245 inches and 0.255 inches

Second Leg Distance Between Hole Centers Along Length:

Between 0.495 inches and 0.505 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.135 inches and 0.145 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.069 inches and 0.730 inches

First Leg Thickness:

Between 0.075 inches and 0.085 inches

Second Leg Thickness:

Between 0.075 inches and 0.085 inches

First Leg Width:

Between 0.770 inches and 0.790 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.518 inches and 0.522 inches

First Leg Distance Between Hole Centers Along Length:

Between 0.310 inches and 0.314 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.125 inches and 0.135 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.405 inches and 0.415 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1020

Material Specification:

Mil-s-7952 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-7952 spec.