

View Online at <https://aerobasegroup.com/nsn/5340-00-532-9889>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.719 inches and 0.781 inches

Second Leg Length:

1.145 inches

Second Leg Width:

Between 1.965 inches and 2.089 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.360 inches

Second Leg Slot Length:

0.570 inches

Second Leg Slot Width:

0.375 inches

First Leg Thickness:

0.056 inches

Second Leg Thickness:

0.056 inches

First Leg Width:

Between 1.964 inches and 2.089 inches

First Leg Corner Radius:

Between 0.219 inches and 0.281 inches

First Leg Distance Between Hole Centers Along Width:

1.527 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.219 inches and 0.281 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.219 inches and 0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0