NSN 5340-00-543-3936

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-543-3936

First Leg Length:

Between 0.615 inches and 0.635 inches

Second Leg Length:

Between 0.680 inches and 0.700 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.194 inches and 0.214 inches

Second Leg Hole Diameter:

Between 0.194 inches and 0.214 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.175 inches and 0.195 inches

First Leg Thickness:

Between 0.053 inches and 0.073 inches

Second Leg Thickness:

Between 0.053 inches and 0.073 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.230 inches and 0.270 inches

Second Leg End Radius:

Between 0.230 inches and 0.270 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

NSN 5340-00-543-3936

Angle Bracket - Page 2 of 2



Material Specification:
Mil-s-18729, cond n military specification single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl3 federal specification all treatment responses
Style Designator:
Angle
Specification Data:
81343-an743+12 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

Mil-std (military Standard): Mil-s-18729 spec.

A042a0