

View Online at <https://aerobasegroup.com/nsn/5340-00-543-3936>

**First Leg Length:**

Between 0.615 inches and 0.635 inches

**Second Leg Length:**

Between 0.680 inches and 0.700 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.194 inches and 0.214 inches

**Second Leg Hole Diameter:**

Between 0.194 inches and 0.214 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.175 inches and 0.195 inches

**First Leg Thickness:**

Between 0.053 inches and 0.073 inches

**Second Leg Thickness:**

Between 0.053 inches and 0.073 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.230 inches and 0.270 inches

**Second Leg End Radius:**

Between 0.230 inches and 0.270 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-18729, cond n military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl3 federal specification all treatment responses

**Style Designator:**

Angle

**Specification Data:**

81343-an743+12 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-18729 spec.