

View Online at <https://aerobasegroup.com/nsn/5340-00-545-2193>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.060 inches and 1.080 inches

Second Leg Length:

Between 1.124 inches and 1.144 inches

Second Leg Width:

Between 1.709 inches and 1.749 inches

Second Leg Corner Radius:

Between 0.310 inches and 0.330 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

1.089 inches

Second Leg Distance Between Hole Centers Along Length:

0.034 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.310 inches and 0.330 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.310 inches and 0.330 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.240 inches and 0.260 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.240 inches and 0.260 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Special Features:

First leg angle in degrees 100.0 min. 104.0 max.

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0