

View Online at <https://aerobasegroup.com/nsn/5340-00-545-2193>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 1.060 inches and 1.080 inches

**Second Leg Length:**

Between 1.124 inches and 1.144 inches

**Second Leg Width:**

Between 1.709 inches and 1.749 inches

**Second Leg Corner Radius:**

Between 0.310 inches and 0.330 inches

**First Leg Hole Diameter:**

Between 0.216 inches and 0.226 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.089 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.034 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.310 inches and 0.330 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.310 inches and 0.330 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.240 inches and 0.260 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.240 inches and 0.260 inches

**First Leg Style:**

End radius and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Special Features:**

First leg angle in degrees 100.0 min. 104.0 max.

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A042a0