

View Online at <https://aerobasegroup.com/nsn/5340-00-559-8997>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.700 inches and 0.720 inches

**Second Leg Length:**

Between 2.445 inches and 2.465 inches

**Second Leg Width:**

Between 0.550 inches and 0.570 inches

**First Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.280 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.270 inches and 0.290 inches

**First Leg Thickness:**

Between 0.058 inches and 0.066 inches

**Second Leg Thickness:**

Between 0.058 inches and 0.066 inches

**First Leg Width:**

Between 0.550 inches and 0.570 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.280 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.270 inches and 0.290 inches

**First Leg End Radius:**

Between 0.406 inches and 0.469 inches

**Second Leg End Radius:**

Between 0.406 inches and 0.469 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0