

View Online at <https://aerobasegroup.com/nsn/5340-00-560-2978>

Fabrication Method (non-core):

Machined

First Leg Length:

0.950 inches

Second Leg Length:

Between 1.608 inches and 1.640 inches

Second Leg Width:

Between 1.068 inches and 1.132 inches

Second Leg Corner Radius:

Between 0.234 inches and 0.266 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance Between Hole Centers Along Width:

0.600 inches

Second Leg Distance Between Hole Centers Along Length:

0.086 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.234 inches and 0.266 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Thickness:

Between 0.056 inches and 0.062 inches

Second Leg Thickness:

Between 0.056 inches and 0.062 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0