

View Online at <https://aerobasegroup.com/nsn/5340-00-567-6543>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 1.590 inches and 1.610 inches

**Second Leg Length:**

Between 1.722 inches and 1.773 inches

**Second Leg Width:**

Between 1.010 inches and 1.990 inches

**Second Leg Corner Radius:**

Between 0.297 inches and 0.328 inches

**First Leg Slot Length:**

Between 0.990 inches and 1.010 inches

**First Leg Slot Width:**

Between 0.330 inches and 0.350 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.089 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.017 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.297 inches and 0.328 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.280 inches and 0.311 inches

**First Leg Thickness:**

Between 0.085 inches and 0.101 inches

**Second Leg Thickness:**

Between 0.085 inches and 0.101 inches

**First Leg End Width:**

Between 0.770 inches and 0.790 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.422 inches and 0.432 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.660 inches and 0.680 inches

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0