

View Online at <https://aerobasegroup.com/nsn/5340-00-567-6543>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.590 inches and 1.610 inches

Second Leg Length:

Between 1.722 inches and 1.773 inches

Second Leg Width:

Between 1.010 inches and 1.990 inches

Second Leg Corner Radius:

Between 0.297 inches and 0.328 inches

First Leg Slot Length:

Between 0.990 inches and 1.010 inches

First Leg Slot Width:

Between 0.330 inches and 0.350 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

1.089 inches

Second Leg Distance Between Hole Centers Along Length:

0.017 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.311 inches

First Leg Thickness:

Between 0.085 inches and 0.101 inches

Second Leg Thickness:

Between 0.085 inches and 0.101 inches

First Leg End Width:

Between 0.770 inches and 0.790 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.422 inches and 0.432 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.660 inches and 0.680 inches

First Leg Style:

Angle

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0