

View Online at <https://aerobasegroup.com/nsn/5340-00-570-9144>

**First Leg Length:**

0.600 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

0.620 inches

**First Leg Hole Diameter:**

Between 0.217 inches and 0.229 inches

**Second Leg Hole Diameter:**

Between 0.279 inches and 0.291 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

Between 0.055 inches and 0.065 inches

**Second Leg Thickness:**

Between 0.055 inches and 0.065 inches

**Center Section Height:**

0.500 inches

**Center Section Width:**

0.620 inches

**Center Section Thickness:**

Between 0.055 inches and 0.065 inches

**First Leg Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.220 inches

**First Leg End Radius:**

0.440 inches

**Second Leg End Radius:**

0.440 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130 or steel comp 8735

**Material Specification:**

66 federal standard 1st material response or ams 6357 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0