

View Online at <https://aerobasegroup.com/nsn/5340-00-570-9144>

First Leg Length:

0.600 inches

Second Leg Length:

1.000 inches

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

Between 0.217 inches and 0.229 inches

Second Leg Hole Diameter:

Between 0.279 inches and 0.291 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.055 inches and 0.065 inches

Second Leg Thickness:

Between 0.055 inches and 0.065 inches

Center Section Height:

0.500 inches

Center Section Width:

0.620 inches

Center Section Thickness:

Between 0.055 inches and 0.065 inches

First Leg Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg End Radius:

0.440 inches

Second Leg End Radius:

0.440 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 4130 or steel comp 8735

Material Specification:

66 federal standard 1st material response or ams 6357 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0