

View Online at <https://aerobasegroup.com/nsn/5340-00-571-0195>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.344 inches and 1.406 inches

Second Leg Length:

Between 1.469 inches and 1.531 inches

Second Leg Width:

Between 1.719 inches and 1.781 inches

First Leg Hole Diameter:

Between 0.500 inches and 0.504 inches

Second Leg Hole Diameter:

Between 0.406 inches and 0.422 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.990 inches and 1.010 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.365 inches and 0.385 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.719 inches and 0.781 inches

First Leg Thickness:

Between 0.156 inches and 0.219 inches

Second Leg Thickness:

Between 0.156 inches and 0.219 inches

First Leg Width:

Between 1.719 inches and 1.781 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.844 inches and 0.906 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.594 inches and 0.656 inches

First Leg End Radius:

Between 0.594 inches and 0.656 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0