

View Online at <https://aerobasegroup.com/nsn/5340-00-573-9942>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.800 inches and 0.880 inches

**Second Leg Length:**

Between 1.980 inches and 2.060 inches

**First Leg Hole Diameter:**

Between 0.274 inches and 0.288 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.400 inches and 0.440 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.400 inches and 0.440 inches

**Second Leg Slot Length:**

Between 0.480 inches and 0.520 inches

**Second Leg Slot Width:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

Between 0.073 inches and 0.087 inches

**Second Leg Thickness:**

Between 0.073 inches and 0.087 inches

**First Leg Width:**

Between 1.810 inches and 1.890 inches

**First Leg Corner Radius:**

Between 0.230 inches and 0.270 inches

**First Leg Distance Between Hole Centers Along Width:**

1.350 inches

**First Leg Distance Between Hole Centers Along Length:**

0.100 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.230 inches and 0.270 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.230 inches and 0.270 inches

**Second Leg End Radius:**

Between 0.400 inches and 0.440 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0