

View Online at <https://aerobasegroup.com/nsn/5340-00-573-9942>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.800 inches and 0.880 inches

Second Leg Length:

Between 1.980 inches and 2.060 inches

First Leg Hole Diameter:

Between 0.274 inches and 0.288 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.400 inches and 0.440 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.400 inches and 0.440 inches

Second Leg Slot Length:

Between 0.480 inches and 0.520 inches

Second Leg Slot Width:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

Between 0.073 inches and 0.087 inches

Second Leg Thickness:

Between 0.073 inches and 0.087 inches

First Leg Width:

Between 1.810 inches and 1.890 inches

First Leg Corner Radius:

Between 0.230 inches and 0.270 inches

First Leg Distance Between Hole Centers Along Width:

1.350 inches

First Leg Distance Between Hole Centers Along Length:

0.100 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.230 inches and 0.270 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.230 inches and 0.270 inches

Second Leg End Radius:

Between 0.400 inches and 0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0