

View Online at <https://aerobasegroup.com/nsn/5340-00-573-9956>

First Leg Length:

3.204 inches

Second Leg Length:

3.204 inches

Reinforcement Method (non-core):

Gusset center section

Second Leg Width:

Between 2.380 inches and 2.420 inches

Second Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Hole Diameter:

Between 0.337 inches and 0.341 inches

Second Leg Hole Diameter:

Between 0.415 inches and 0.429 inches

Second Leg Distance Between Hole Centers Along Width:

2.075 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.435 inches

First Leg Thickness:

Between 0.115 inches and 0.135 inches

Second Leg Thickness:

Between 0.115 inches and 0.135 inches

First Leg Width:

Between 1.616 inches and 1.896 inches

First Leg Corner Radius:

Between 0.220 inches and 0.280 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.236 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.248 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.320 inches and 0.360 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0