

View Online at <https://aerobasegroup.com/nsn/5340-00-574-8824>

**First Leg Length:**

Between 0.710 inches and 0.772 inches

**Second Leg Length:**

Between 1.064 inches and 1.126 inches

**Second Leg Width:**

Between 1.469 inches and 1.531 inches

**First Leg Hole Diameter:**

Between 0.197 inches and 0.200 inches

**Second Leg Hole Diameter:**

Between 0.610 inches and 0.672 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.719 inches and 0.781 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.500 inches and 0.562 inches

**First Leg Thickness:**

0.085 inches

**Second Leg Thickness:**

0.085 inches

**First Leg Width:**

Between 1.469 inches and 1.531 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 0.969 inches and 1.031 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**Second Leg End Radius:**

Between 0.500 inches and 0.562 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6370 assn standard single material response or sae 4130 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, class 2 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0