

View Online at <https://aerobasegroup.com/nsn/5340-00-574-8824>

First Leg Length:

Between 0.710 inches and 0.772 inches

Second Leg Length:

Between 1.064 inches and 1.126 inches

Second Leg Width:

Between 1.469 inches and 1.531 inches

First Leg Hole Diameter:

Between 0.197 inches and 0.200 inches

Second Leg Hole Diameter:

Between 0.610 inches and 0.672 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.719 inches and 0.781 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.500 inches and 0.562 inches

First Leg Thickness:

0.085 inches

Second Leg Thickness:

0.085 inches

First Leg Width:

Between 1.469 inches and 1.531 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

Between 0.969 inches and 1.031 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

Between 0.500 inches and 0.562 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6370 assn standard single material response or sae 4130 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0