

View Online at <https://aerobasegroup.com/nsn/5340-00-576-3255>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.696 inches and 0.728 inches

Second Leg Length:

Between 1.630 inches and 1.650 inches

Second Leg Width:

Between 0.550 inches and 0.570 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

Center Section Height:

Between 0.490 inches and 0.510 inches

Center Section Width:

Between 0.550 inches and 0.570 inches

Center Section Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.550 inches and 0.570 inches

First Leg Distance From Edge To Hole Center Along Width:

0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

Second Leg End Radius:

0.280 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

99.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0