

View Online at <https://aerobasegroup.com/nsn/5340-00-576-9086>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.670 inches and 0.690 inches

Second Leg Length:

Between 1.270 inches and 1.290 inches

Second Leg Width:

Between 0.550 inches and 0.570 inches

First Leg Hole Diameter:

Between 0.214 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.280 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.270 inches and 0.290 inches

First Leg Thickness:

Between 0.046 inches and 0.054 inches

Second Leg Thickness:

Between 0.046 inches and 0.054 inches

First Leg Width:

Between 0.550 inches and 0.570 inches

First Leg Distance From Edge To Hole Center Along Width:

0.280 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.270 inches and 0.290 inches

First Leg End Radius:

Between 0.406 inches and 0.469 inches

Second Leg End Radius:

Between 0.406 inches and 0.469 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 4130

Material Specification:

Ams 6350 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0