

View Online at <https://aerobasegroup.com/nsn/5340-00-576-9964>

First Leg Length:

Between 1.938 inches and 2.062 inches

Second Leg Length:

8.812 inches

Second Leg Width:

3.000 inches

First Leg Hole Diameter:

0.438 inches

Second Leg Hole Diameter:

0.438 inches

Second Leg Distance Between Hole Centers Along Width:

Between 1.734 inches and 1.766 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.235 inches and 1.265 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

3.000 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.734 inches and 1.766 inches

First Leg Distance From Edge To Hole Center Along Width:

0.625 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.813 inches and 0.937 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Mil-s-20166, type u, grade m military specification single material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Mil-p-6808 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-20166 spec.