NSN 5340-00-576-9964

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-576-9964

First Leg Length:
Between 1.938 inches and 2.062 inches
Second Leg Length:
8.812 inches
Second Leg Width:
3.000 inches
First Leg Hole Diameter:
0.438 inches
Second Leg Hole Diameter:
0.438 inches
Second Leg Distance Between Hole Centers Along Width:
Between 1.734 inches and 1.766 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.625 inches
Second Leg Distance From Edge To Hole Center Along Length:
Between 1.235 inches and 1.265 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
First Leg Width:
3.000 inches
First Leg Distance Between Hole Centers Along Width:
Between 1.734 inches and 1.766 inches
First Leg Distance From Edge To Hole Center Along Width:
0.625 inches
First Leg Distance From Edge To Hole Center Along Length:
Between 0.813 inches and 0.937 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
First Leg Angle:
90.0 degrees

Material:

Steel

Material Specification:

Mil-s-20166, type u, grade m military specification single material response

NSN 5340-00-576-9964 Angle Bracket - Page 2 of 2

Mil-s-20166 spec.



Surface Treatment:
Zinc
Surface Treatment Specification:
Mil-p-6808 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):