

View Online at <https://aerobasegroup.com/nsn/5340-00-582-3350>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.748 inches

Second Leg Length:

0.685 inches

Reinforcement Method (non-core):

Gusset both sides

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

Between 0.118 inches and 0.138 inches

Second Leg Hole Diameter:

Between 0.194 inches and 0.214 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

0.750 inches

First Leg Distance Between Hole Centers Along Width:

0.370 inches

First Leg Distance From Edge To Hole Center Along Width:

0.190 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg End Radius:

0.440 inches

Second Leg End Radius:

0.440 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5, alclad t4 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0