

View Online at <https://aerobasegroup.com/nsn/5340-00-582-3975>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.530 inches and 0.550 inches

Second Leg Length:

0.710 inches

Second Leg Width:

1.420 inches

First Leg Hole Diameter:

0.281 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.710 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Thickness:

Between 0.071 inches and 0.085 inches

Second Leg Thickness:

Between 0.071 inches and 0.085 inches

First Leg Width:

1.420 inches

First Leg Corner Radius:

Between 0.200 inches and 0.220 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.200 inches and 0.220 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.200 inches and 0.220 inches

Second Leg End Radius:

0.710 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

B50t13a, general electric co. Mfr ref single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0