

View Online at <https://aerobasegroup.com/nsn/5340-00-584-1775>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.780 inches and 0.820 inches

Second Leg Length:

Between 0.960 inches and 1.000 inches

Second Leg Width:

Between 0.520 inches and 0.600 inches

First Leg Hole Diameter:

0.344 inches

Second Leg Hole Diameter:

0.219 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.300 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.220 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

0.520 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.260 inches and 0.300 inches

First Leg Distance From Edge To Hole Center Along Length:

0.260 inches

First Leg End Radius:

Between 0.380 inches and 0.410 inches

Second Leg End Radius:

Between 0.380 inches and 0.410 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

93.5 degrees

Special Features:

First leg angle in degrees 100.0 min. 104.0 max.

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0