NSN 5340-00-584-6343

Rod End Clevis - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5340-00-584-6343 |
|---|
| Thread Class: |
| 3a rod connection |
| Thread Direction: |
| Right-hand rod connection |
| Thread Length: |
| 1.080 inches rod connection |
| Shank Length: |
| Between 1.140 inches and 1.160 inches |
| Hole Diameter: |
| Between 0.191 inches and 0.192 inches |
| Shank Diameter: |
| 0.250 inches |
| Overall Height: |
| Between 0.490 inches and 0.510 inches |
| Overall Width: |
| Between 0.410 inches and 0.430 inches |
| Metallic Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Fork Span Width: |
| Between 0.252 inches and 0.256 inches |
| Securing Pin Hole Diameter: |
| Between 0.065 inches and 0.075 inches |
| Distance From Pivot Pinhole Center To Rod Connection End: |
| Between 1.820 inches and 1.840 inches |
| Fork Arm Thickness: |
| 0.079 mils and 0.087 centimeters |
| Fork Depth: |
| Between 0.575 inches and 0.585 inches |
| Thread Size: |
| 0.250 inches rod connection |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Clevis |
| Thread Series Designator: |
| Unf rod connection |
| Shelf Life: |

N/a

NSN 5340-00-584-6343

Rod End Clevis - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A264a0