## NSN 5340-00-584-9484

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-584-9484

Falscian tan Mathad (nan asaa)
Fabrication Method (non-core):
Wrought
First Leg Length:
1.125 inches
Second Leg Length:
1.369 inches
Second Leg Width:
0.500 inches
First Leg Hole Diameter:
Between 0.217 inches and 0.225 inches
Second Leg Hole Diameter:
Between 0.279 inches and 0.288 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
Between 0.056 inches and 0.068 inches
Second Leg Thickness:
Between 0.056 inches and 0.068 inches
Center Section Height:
0.750 inches
Center Section Width:
0.500 inches
Center Section Thickness:
Between 0.056 inches and 0.068 inches
First Leg Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg End Radius:
0.500 inches
Second Leg End Radius:
0.500 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
One hole
Second Leg Style:

End radius

## NSN 5340-00-584-9484

Double Angle Bracket - Page 2 of 2



Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Steel
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A042a0