

View Online at <https://aerobasegroup.com/nsn/5340-00-590-7519>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.910 inches and 0.950 inches

**Second Leg Length:**

Between 0.940 inches and 0.960 inches

**Second Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.285 inches and 0.295 inches

**Second Leg Slot Length:**

Between 0.310 inches and 0.330 inches

**Second Leg Slot Width:**

Between 0.214 inches and 0.224 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

Between 0.490 inches and 0.510 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.422 inches and 0.453 inches

**Second Leg End Radius:**

Between 0.422 inches and 0.453 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 4130

**Material Specification:**

Ams 6350 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0