

View Online at <https://aerobasegroup.com/nsn/5340-00-592-7785>

Fabrication Method (non-core):

Machined

First Leg Length:

1.393 inches

Second Leg Length:

1.755 inches

Second Leg Width:

2.000 inches

Second Leg Corner Radius:

0.455 inches

First Leg Hole Diameter:

Between 0.339 inches and 0.349 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.455 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.775 inches

Second Leg Slot Length:

Between 0.030 inches and 0.040 inches

Second Leg Slot Width:

Between 0.390 inches and 0.400 inches

First Leg Thickness:

Between 0.085 inches and 0.101 inches

Second Leg Thickness:

Between 0.085 inches and 0.101 inches

First Leg Width:

2.519 inches

First Leg Corner Radius:

0.281 inches

First Leg Distance Between First And Second Hole Centers Along Width:

0.977 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

0.980 inches

First Leg Distance From Edge To Hole Center Along Width:

0.281 inches

First Leg Distance From Edge To Hole Center Along Length:

0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Special Features:

Second leg contains two vertical slots

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0