

View Online at <https://aerobasegroup.com/nsn/5340-00-593-3195>

**Thread Class:**

3a rod connection

**Thread Direction:**

Right-hand rod connection

**Thread Length:**

1.031 inches rod connection

**Shank Length:**

1.125 inches

**Hole Diameter:**

Between 0.4365 inches and 0.4385 inches

**Shank Diameter:**

0.312 inches

**Overall Width:**

Between 0.718 inches and 0.728 inches

**End Radius:**

0.437 inches

**Metallic Hardness Rating:**

39.0 rockwell c and 42.0 rockwell c

**Fork Span Width:**

Between 0.500 inches and 0.510 inches

**Distance From Pivot Pinhole Center To Rod Connection End:**

1.812 inches

**Fork Arm Thickness:**

0.109 inches

**Fork Depth:**

0.468 inches

**Thread Size:**

0.312 inches rod connection

**Criticality Code Justification:**

Aaub

**Special Features:**

Shank grooved 0.062 in min, 0.067 in maximum w, 0.052 in min, 0.057 in maximum deep, 0.812 in min, 0.0843 in maximum lg

**Material:**

Steel comp 8740

**Material Specification:**

Mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

**Style Designator:**

Clevis

**Thread Series Designator:**

Unf rod connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A264a0

**Mil-std (military Standard):**

Mil-s-6049 spec.