

View Online at <https://aerobasegroup.com/nsn/5340-00-593-3195>

Thread Class:

3a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

1.031 inches rod connection

Shank Length:

1.125 inches

Hole Diameter:

Between 0.4365 inches and 0.4385 inches

Shank Diameter:

0.312 inches

Overall Width:

Between 0.718 inches and 0.728 inches

End Radius:

0.437 inches

Metallic Hardness Rating:

39.0 rockwell c and 42.0 rockwell c

Fork Span Width:

Between 0.500 inches and 0.510 inches

Distance From Pivot Pinhole Center To Rod Connection End:

1.812 inches

Fork Arm Thickness:

0.109 inches

Fork Depth:

0.468 inches

Thread Size:

0.312 inches rod connection

Criticality Code Justification:

Aaub

Special Features:

Shank grooved 0.062 in min, 0.067 in maximum w, 0.052 in min, 0.057 in maximum deep, 0.812 in min, 0.0843 in maximum lg

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0

Mil-std (military Standard):

Mil-s-6049 spec.