

View Online at <https://aerobasegroup.com/nsn/5340-00-594-4106>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.2825 inches and 0.4105 inches

Second Leg Length:

0.563 inches

Second Leg Width:

1.100 inches

Second Leg Corner Radius:

0.125 inches

Second Leg Hole Diameter:

Between 0.143 inches and 0.145 inches

Second Leg Distance Between Upper Hole Centers Along Width:

Between 0.686 inches and 0.690 inches

Second Leg Distance Between Lower Hole Centers Along Width:

Between 0.686 inches and 0.690 inches

Second Leg Distance Between Hole Centers Along Length:

0.219 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 0.030 inches and 0.032 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.125 inches

First Leg Thickness:

Between 0.0605 inches and 0.0675 inches

Second Leg Thickness:

Between 0.0605 inches and 0.0675 inches

Center Section Height:

0.718 inches

Center Section Width:

1.000 inches

Center Section Thickness:

Between 0.0605 inches and 0.0675 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.125 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

No hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

Three slits in first leg; holes adjacent to second leg lg 0.087 in. Min 0.091 in. Maximum dia; additional 0.180 in. Nom diameter hole in second leg on 0.500 in. Centerline; one hole 0.093 dja countersunk to 0.109 in. Diameter on both sides located on center section

Material:

Copper alloy 511

Material Specification:

Astm b103 assn standard single material response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0