

View Online at <https://aerobasegroup.com/nsn/5340-00-596-4923>

Thread Class:

2a rod connection

Thread Direction:

Right-hand rod connection

Thread Length:

2.750 inches rod connection

Shank Length:

3.100 inches

Hole Diameter:

Between 0.312 inches and 0.318 inches

Shank Diameter:

Between 0.739 inches and 0.748 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

End Radius:

0.940 inches

End Application:

Uaircraft, b-2 bomber (atb), support equipment, t-37aircraft, support equipment, t-38 aircraft, engine, aircraft, f110-ge-100/129 (f-16c/d), aircraft, stratolifter c-135, support equipment, f-106 aircraft, aircraft, thunderbolt ii, a-10

Fork Span Width:

Between 0.995 inches and 1.010 inches

Securing Pin Hole Diameter:

Between 0.312 inches and 0.318 inches

Distance From Center Of Securing Pin Hole To Rod End:

5.880 inches

Distance From Pivot Pinhole Center To Rod Connection End:

5.880 inches

Fork Arm Thickness:

0.377 inches

Fork Depth:

2.000 inches

Thread Size:

0.750 inches rod connection

Material:

Steel comp 1212 or steel comp 5015

Material Specification:

Aisi/sae assn standard 1st material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 1 federal specification single treatment response

Style Designator:

Clevis

Thread Series Designator:

Unf rod connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A264a0