NSN 5340-00-598-3218

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-598-3218

Cross Sectional Shape:
Oblong recess
Hole Diameter:
0.531 inches
Width:
4.562 inches
Flange Thickness:
0.078 inches
Edge Shape:
Rectangle, multi holes
Length:
31.812 inches
Inside Width:
3.000 inches
Inside Length:
30.250 inches
Corner Radius:
1.375 inches
Hole Quantity Along Length:
4
Distance From First Hale Contarline To Find Along Langth.
Distance From First Hole Centerline To End Along Length:
1.969 inches
1.969 inches
1.969 inches Distance From First Hole Centerline To End Along Width:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material:
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Steel
1.969 inches Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Steel Fsc Application Data:
Distance From First Hole Centerline To End Along Width: 2.188 inches First Recess Inside Height: 0.625 inches Inside Corner Radius: 3.750 inches Body Thickness: 0.078 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Steel Fsc Application Data: Diesel engines

--

NSN 5340-00-598-3218

Access Cover - Page 2 of 2



Demilitarization:

No

Fiig:

A531c0