

View Online at <https://aerobasegroup.com/nsn/5340-00-598-5629>

Fabrication Method (non-core):

Machined

First Leg Length:

1.063 inches

Second Leg Length:

2.000 inches

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

Between 0.201 inches and 0.209 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.413 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg Thickness:

Between 0.055 inches and 0.065 inches

Second Leg Thickness:

Between 0.055 inches and 0.065 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.375 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 1010

Material Specification:

Ams 5040 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0