

View Online at <https://aerobasegroup.com/nsn/5340-00-598-6366>

**End Application:**

Metal chair socket

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

Not rated

**Stem Style:**

Friction ring

**Stem Length:**

Between 1.125 inches and 1.500 inches

**Stem Diameter:**

0.375 inches

**Material And Location:**

Rubber, hard wheel rim and fiber wheel rim and rubber, soft tread and steel body

**Surface Treatment And Location:**

Nickel body

**Wheel Type:**

Built up

**Wheel Diameter:**

Between 1.625 inches and 1.750 inches

**Effective Height:**

2.625 inches

**Wheel Bearing Type:**

Plain, self-lubricated

**Swivel Bearing Type:**

Ball

**Swivel Bearing Arrangement:**

One row or two row

**Special Features:**

Nonstaining, nonmarking cushion treads, permanently bonded, impact resistant, hard rubber composition core; wheels tread thickness 3/16in.; wheel tread and core material hardness range hard rubber 55-75 shore d, soft rubber 55-70 shore a; tensile 1500 psi min., adhesion between tread and core is 50 lbs per inch of width; axles and stems - cold drawn steel, nut and bolt combination or solid rivet type and permanently fastened; ball bearings - corrosion resistant, case hardened ground steel, assembly with a water repellent grease

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600