

View Online at <https://aerobasegroup.com/nsn/5340-00-598-6905>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 1.023 inches and 1.097 inches

Second Leg Length:

Between 1.461 inches and 1.533 inches

Second Leg Width:

Between 0.734 inches and 0.766 inches

First Leg Hole Diameter:

Between 0.194 inches and 0.209 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.419 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.359 inches and 0.391 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.359 inches and 0.391 inches

First Leg Thickness:

Between 0.055 inches and 0.065 inches

Second Leg Thickness:

Between 0.055 inches and 0.065 inches

First Leg Width:

Between 0.734 inches and 0.766 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.359 inches and 0.391 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.359 inches and 0.391 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

Second Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Fms-61100, allison div general motors mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0